Environmental Data Sheet

ECOSYS P2040dn (from serial number VCY6Z32849)

Environmental Management	This device is manufactured in production facilities that work with an environmental management system in accordance with ISO 14001.			
Power Consumption Heat Emission	Maximum (at switch o Printing: Ready: Sleep-mode: Off-mode:	n, full options) 974 W 350 620 W 223 8.0 W 29 I 0.8 W 2.9 0.1 W 0.4	06 kJ/h 32 kJ/h kJ/h kJ/h	
Typical Power Consumption (TEC) (according to ENERGY STAR 3.0)	0.45 kWh/week (4000 pages/week)			
Installation Notes	The printer should be placed in a way, that there is adequately space for operation and maintenance on both sides, as well as in front and behind the system. Provide adequate ventilation. Do not set up the printer in dusty rooms, and protect against ammonia vapours. Please follow the instructions in the user manual.			
Humidity	10% - 80%			
Room Temperature	10°C - 32.5°C			
Noise Emission (according to ISO 7779)	Surface sound pressur (measurement in 1m of [dB(A) L _{pA}] Operator position [dB(A) L _{pA}] Sound power level (DB	distance, avera 49.6 56.1	Ready ge of single me not measurable not measurable	Quiet-Mode asurements) 45.5 51.1
	[dB(A) L _{WAd}]	65.1		
Light Source	Exposure drum: Laser			
Emission	According to DE-UZ 2: TVOC (Operation): TVOC (Ready): Benzene: Styrene: Ozone: Dust:	1.9 mg/h 0.039 mg/h < limit of qu < limit of qu	1.9 mg/h 0.039 mg/h < limit of quantitation < limit of quantitation < limit of quantitation	
ECOlabel	Exposure drum: Laser Product related environmental labels in Germany/Austria: Blue Angel DE-UZ 219 Status: Awarded List of certified KYOCERA products can be found here: https://www.blauer-engel.de/en/products/company/kyocera-document-solutions-deutschland-gmbh-only-de-at Others countries: Please refer to the local country information.			

effective 12/2021 – Errors and omissions excepted

